

PRODUCT DATA SHEET



Characteristic	Description
General	
Product Name	TRAKMARK DURA
Product Type	High Solids Water Based Acrylic Paint
Colour	White / Yellow / Red / Blue / Green / Black
Specification	IS 164 / TP-P 1952 F (Federal Specifications)
Application	Airless Spray
Physical Characteristics	
Drying Time	5 – 10 Minutes Touch Dry
Viscosity at 30 °C	> 95 kU
% NVM	> 60%
Minimum Thickness	100 Micron
Mass in Kg / Ltr	1.4 ± 0.05 Kg / Ltr
Coverage	2.1 – 2.5 m ² / Ltr at WFT 400 Micron
Packaging	
15 Ltr Standard Packaging.	
Storage	
Shelf Life is approx. 12 Months from Manufacturing subject to material being stored in moisture free, dry conditions without opening the packaging.	
Areas of Application	
<ul style="list-style-type: none"> • Concrete Kerbs & Crash Barriers • Airfield Markings • Parking Lots • Temporary Horizontal Markings 	

Application Safeguards

- Mechanical mixing of contents recommended before use.
- Filter the material if required before use.
- The surface to be marked shall be clear of dirt, dust, debris.
- Any curing compounds / putty / previous surface coatings must be stripped off prior to application
- New Concrete / Asphalt should be allowed to cure for a minimum 20 days to maximize adhesion and durability
- Ensure surface ambient temperature is more than 10°C
- Use Potable water for dilution

Safety Recommendations

- Store in cool dry environment
- Avoid contact with eatables. If ingested seek immediate medical attention.
- Recommended disposal of empty buckets as per good engineering practices and environmental policies

Post Application Care

For best results ensure traffic is not allowed on the road for a minimum duration of 1 hour after application and complete drying of material.